



Technical University of Lodz
Institute of Electronics

Algorithms and Data Structures

6. Strings and Text Manipulation I

Łódź 2013





Exercise

- Type in the program; Save it as **textManipulation.py**; Run the script

```
1  # string and text manipulation 1
2
3  ▼ def countChar(text, myChar):
4      """Functions counts appearance of myChar in the text"""
5      count = 0
6      ▼ for c in text:
7          ▼ if c == myChar:
8              count +=1
9      - print 'Character %s appears %d time(s) in the string "%s"'%(myChar,count,text)
10
11  ▼ def insertTextNTimes(text, pos, insertText, n):
12      """Function insert insertText n times into Text at a position pos"""
13      - return text[:pos] + insertText*n + text[pos:]
14
15  ▼ def main():
16      sentence = 'Ala ma kota'
17      charToFind = 'a'
18      textToInsert = ' i Ola'
19
20      countChar(sentence, charToFind)
21      - print insertTextNTimes(sentence, 3, textToInsert, 4)
22
23  main()
```



Strings

- **String** is a basic type in Python
- **String** is an example of data structure
- **String** is a collection of data organized to efficiently support a particular set of access methods and operations
- **String** is a sequence of characters inside quotation marks
 1. Single quotes ('')
 2. Double quotes ("")
 3. Triple quotes – for multi-line strings (""")

```
>>> subject = 'Algorithms and Data Structures'
```

```
>>> name = "Grzegorz"
```

```
>>> surname = "Brzeczyszczkiewicz"
```

```
>>> multi_line_string = """This is a very long string, that is spread across many, many lines, for  
example a description of some newly created function """
```



Basic operations

Concatenation

```
>>> letters = "ab" + "cd"
>>> letters += 'ab'
>>> "Ala" + ' ma ' + "kota!"
```

$s1 + s2$ The string $s1$ followed by $s2$
 $s1 += s2$ Shorthand for $s1 = s1 + s2$

Repetition

```
>>> "Hello"*4
>>> "bye!"*7
>>> 10*" - *-? - *"
```

$s*n$ The string $s+s+\dots+s$, n times
 $n*s$ The same as $s*n$

String Accumulators

```
>>> s = 'a'
>>> for i in range(4):
>>>     s += 'b'
```

$\langle \text{accumulator} \rangle = \langle \text{string value} \rangle$
loop:
 $\langle \text{accumulator} \rangle += \langle \text{string to add} \rangle$

Comparison

```
>>> s1 = 'ala'; s2 = 'ala'; s3 = 'ola'
>>> s1 == s2
>>> s1 == s3
```


$s1 == s2$ returns True
 $s1 == s3$ returns False



Indexing

```
>>> text = 'Biomedical Eng.'
```


The *text* variable is stored in a memory like below. Each, individual character is stored in consecutive memory location



Each number along the bottom row is called **index** of the character above it.



Indexing



Type in following commands and check the result:


```
>>> text[0] = ?  
>>> text[1] = ?  
>>> text[5] = ?  
>>> text[8] = ?  
>>> text[11] = ?
```

string[i] Character at index i.

Indexing a string always returns a single character



Indexing



Type in following commands and check the result:

```
>>> text[-1] = ?  
>>> text[-5] = ?  
>>> text[-7] = ?  
>>> text[-11] = ?  
>>> text[-15] = ?
```

string[i] Character at index i.


Indexing a string always returns a single character



Slicing

Accessing a group of consecutive characters

`text[i:j]` Slice from *i* to *j*-1




```
>>> text[0:3] = ?  
>>> text[3:6] = ?  
>>> text[11:14] = ?  
>>> text[0:15] = ?
```

Does not include `text[j]`!



Slicing



```
>>> text[:3] = ?  
>>> text[3:] = ?  
>>> text[:] = ?
```

text[:j] Slice from beginning to j-1
text[i:] Slice from i to the end
text[:] Full slice, which creates a copy of s

Optional third parameter k specifies a stepsize other 1 (see the range() function)

```
>>> text[2:12:2] = ?  
>>> text[3::3] = ?  
>>> text[::-2] = ?  
>>> text[::-1] = ?  
>>> text[9:2:-1] = ?  
>>> text[:5:-1] = ?  
>>> text[5::-1] = ?
```

If k is negative, the index i will still be the starting point.
If i is omitted with k<0, the beginning is considered the right end (index-1), and if j is omitted with a k<0, the end is at the left (index 0)



In and Not In

To test whether or not a characters in *x* are a substring of *s*. Substring means that the characters of *x* occur as a consecutive slice of *s*

<i>x</i> in <i>s</i>	True if <i>x</i> is a substring of <i>s</i> ; otherwise False
<i>x</i> not in <i>s</i>	True if <i>x</i> is not a substring of <i>s</i> ; otherwise True

```
>>> s = 'ala ma kota'
```

```
>>> 'a' in s = ?  
>>> 'ala' in s = ?  
>>> 'a ma k' in s = ?  
>>> 'alama' in s = ?  
>>> 'kot' in s = ?
```

```
>>> 'a' not in s = ?  
>>> 'ala' not in s = ?  
>>> 'ma ' not in s = ?  
>>> 'alama' not in s = ?  
>>> 'ola' not in s = ?
```



Length

Length and type of the string

```
>>> len(subject)
>>> len(text)
>>> type(name)
>>> type(student1)
```

len(string)

type(object)

What character is at the index 15?

```
>>> text[15]
```

```
----> 1 text[15]
```

IndexError: string index out of range

The first character of text is `text[0]`, not `text[1]`. Remember that in programming, counting usually starts at 0, not 1.

The “type” of the error that occurred

Short message about why it occurred



Changing characters

Suppose we have a string

```
>>> day = 'Today is Monday'
```

We want to repair spelling mistake

```
>>> day[4] = 'y'
```

Python strings are immutable

```
----> 1 day[4]='y'
```

```
TypeError: 'str' object does not support item assignment
```

The “type” of the error that occurred

Short message about why it occurred

We have to create a string and assign it to day

```
>>> day = day[:4] + 'y' + day[5:]
```

```
>>> print day
```



Looping

If we want to scan through a string one character at a time we can use a **for loop**

```
>>> day = 'Today is Monday'
```

```
for <variable> in <string>: # loop over each character
    <body>
```

The easiest way is as follows
(without holding the current location
in the string)

```
>>> for c in day:
    print c
```

Use comma at the end of
print() command. What was
changed?

```
>>> for c in day:
    print c,
```

Task: create string like below:

```
>>> T * o * d * a * y *   * i * s *   * M * o * n * d * a * y *
```



Looping

If we want to scan through a string with information about current location

```
>>> day = 'Today is Monday'
```

Let's recall the for loop syntax

```
for <variable> in <sequence>:  
    <body>
```

```
>>> for i in range(5):  
    print i,
```

```
>>> 0 1 2 3 4
```

How define a scope of a `range()` function?

```
>>> for i in range(???):  
    print i,
```

The scope of a `range()` is the length of a string

```
>>> for i in range(len(day)):  
    print i,
```

```
>>> 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
```

How to get a single character from the string?

```
>>> for i in range(len(day)):  
    print day[i],
```

```
>>> T o d a y   i s   M o n d a y
```

Task: create strings (below, and on the right):

```
>>> i s   M o n d a y
```

```
0 -> T  
1 -> o  
2 -> t  
3 -> a  
4 -> y  
5 ->  
6 -> i  
7 -> s  
8 ->  
9 -> M  
10 -> o  
11 -> n  
12 -> d  
13 -> a  
14 -> y
```



Exercise

6.0 Fill in the red gaps in the body of the function `deleteChar(text, myChar)`

```
1 # string and text manipulation 1 - exercises
2
3 ▼ def deleteChar(text, myChar):
4     """Function deletes first appearance of a given character"""
5     ▼ for i in range(len(text)):
6         ▼ if [red] == myChar:
7             text1 = text[red] + text[red]
8             break #comment this line, what is the difference?
9         ▼ else:
10             text1 = text
11             return text1
```



Exercises

6.1 Write a Python script to print a patterns like shown below
(Hint: use for loop and string repetition, use 10 stars).

A)

```
*
**
***
****
*****
*****
*****
*****
*****
*****
*****
```

B)

```
*****
*****
*****
*****
*****
*****
*****
*****
*****
*****
*****
```




Exercises

6.2 Determine the values of these expressions:

```
>>> subject = "Algorithms and Data Structures"
```

```
subject[0]  
subject[5:]  
subject[:5]  
subject[::2]
```

```
subject[1:5]  
subject[:-4]  
subject[-15:]  
subject[-20:20]
```

6.3 Create Python expressions using variable `subject` that have these values:

```
>>> subject = "Algorithms and Data Structures"
```

```
Algorithms  
Data  
Structures  
Alg
```

```
serutcurtS ataD dna smhtiroglA  
AotsnDatcr #every third  
suust amig #every third negative dir.  
smhtiroglA #algorithms neg.
```



Exercises

6.4 Write a script **email.py** that builds e-mail address for a student. Ask the user for booth first and second name and surname. Generate e-mail address with the use of pattern: initials@p.lodz.pl, e.g. mmk@p.lodz.pl

6.5 Write a script `stringAccumlator1.py` that accumulates characters until 'q' appear

6.6 Write a script `stringAccumlator2.py` that accumulates characters until string 'quit' appear

6.7 Write a script *myStringFunctions.py*. In the script write a function `stringAccumlator(someText)` that accumulates every 2nd (or 3rd) character from `someText`



Exercises

6.8 In the script *myStringFunctions.py* write a function `stringReverse(someText)` that returns reversed `someText`

6.9 In the script *myStringFunctions.py* write a function `getSpaces(someText)` that returns number of spaces and index of the last space

6.10 In the script *myStringFunctions.py* write a function `vowelsConsonantsAndSpaces(someText)` that returns number of vowels, consonants and spaces in the `someText`

6.11 In the script *myStringFunctions.py* create a function `replaceSpaces(someText, newChar)` that replaces the spaces with the `newChar` given as an argument.



Exercises

6.12 In the script *myStringFunctions.py* create a function `replaceCharacter(someText, charToReplace, newChar)` that replaces the specified char (`charToReplace`) in `someText` with the `newChar` given as an argument

6.13 In the script *myStringFunctions.py* create a function `deleteReplaceTripleCharacter(someText, charToChange, flag)` that depends on flag value replaces/delete/triples given `charToChange`. The help of the function is as follows:

```
""" Function deletes, replace with space or triple given letter (character)
```

```
depends on flag value:
```

```
    d -> delete
```

```
    s -> replace with space
```

```
    t -> triple
```

```
Usage:
```

```
1)deleteReplaceTripleCharacter('Biomedical','m','d') -> 'Bioedical'
```

```
2)deleteReplaceTripleCharacter('Biomedical','m','s') -> 'Bio edical'
```

```
3)deleteReplaceTripleCharacter('Biomedical','m','t') -> 'Biommmmedical'
```

```
"""
```



Summary

1. String is a sequence of characters inside quotation marks
2. Strings can be added, repeated, accumulated and compared
3. A indexing method is used to get individual character from a string
4. Python strings can have positive and negative indexes
5. To get several characters from a string we use slicing
6. Boolean values are returned by In and Not In operators
7. To change a character inside string we have to create a new
8. To scan through a string we use for loop



Literature

Brian Heinold, Introduction to Programming Using Python, Mount St. Mary's University, 2012 (<http://faculty.msmary.edu/heinold/python.html>).

Brad Dayley, Python Phrasebook: Essential Code and Commands, SAMS Publishing, 2007 (dostępne też tłumaczenie: B. Dayley, Python. Rozmówki, Helion, 2007).

Mark J. Johnson, A Concise Introduction to Programming in Python, CRC Press, 2012.